

Non-Condensing Residential/Light Duty Commercial Gas

Altitude Range (Feet Above Sea Level) 0-6,000 Feet

| Model Number | Type | BTU Input Natural/Propane | | Energy Factor (E.F.) | | Annual Operating Cost | | Hot Water Output (GPM) | | |
|--------------|---------|---------------------------|---------|----------------------|---------|-----------------------|---------|------------------------|-----------|-----------|
| | | Minimum | Maximum | Natural | Propane | Natural | Propane | Maximum | 45°F Rise | 70°F Rise |
| GTU-110-NI | Indoor | 19,500 | 140,000 | 0.82 | 0.82 | \$199 | \$482 | 6.6 | 5.1 | 3.3 |
| GTU-310-NI | Indoor | 11,000 | 190,000 | 0.82 | 0.82 | \$199 | \$482 | 8.0 | 6.9 | 4.4 |
| GTU-510-NI | Indoor | 11,000 | 199,000 | 0.82 | 0.82 | \$199 | \$482 | 10.0 | 7.2 | 4.7 |
| GTU-110-NE | Outdoor | 19,500 | 140,000 | 0.82 | 0.82 | \$199 | \$482 | 6.6 | 5.1 | 3.3 |
| GTU-310-NE | Outdoor | 11,000 | 190,000 | 0.82 | 0.82 | \$199 | \$482 | 8.0 | 6.9 | 4.4 |
| GTU-510-NE | Outdoor | 11,000 | 199,000 | 0.82 | 0.82 | \$199 | \$482 | 10.0 | 7.2 | 4.7 |

*For propane, change N to P in the model number when ordering. Example: GTU-110-PI

Non-Condensing Residential/Light Duty Commercial Gas Ultra Low NOx Models

Suitable for Use in High Altitude Areas: Altitude Range (Feet Above Sea Level) 0-7,500 Feet

| Model Number | Type | BTU Input Natural | | Energy Factor (E.F.) | Annual Operating Cost | Hot Water Output (GPM) | | |
|--------------|---------|-------------------|---------|----------------------|-----------------------|------------------------|-----------|-----------|
| | | Minimum | Maximum | Natural | Natural | Maximum | 45°F Rise | 70°F Rise |
| GTU-110-UI | Indoor | 15,000 | 140,000 | 0.82 | \$199 | 6.6 | 5.1 | 3.3 |
| GTU-310-UI | Indoor | 15,000 | 190,000 | 0.82 | \$199 | 8.0 | 6.9 | 4.4 |
| GTU-510-UI | Indoor | 15,000 | 199,000 | 0.82 | \$199 | 10.0 | 7.2 | 4.7 |
| GTU-110-UE | Outdoor | 15,000 | 140,000 | 0.82 | \$199 | 6.6 | 5.1 | 3.3 |
| GTU-310-UE | Outdoor | 15,000 | 190,000 | 0.82 | \$199 | 8.0 | 6.9 | 4.4 |
| GTU-510-UE | Outdoor | 15,000 | 199,000 | 0.82 | \$199 | 10.0 | 7.2 | 4.7 |

Ultra Low NOx is only available in Natural Gas.

Condensing Residential/Light Duty Commercial Gas

Suitable for Use in High Altitude Areas: Altitude Range (Feet Above Sea Level) 0-10,100 Feet

| Model Number | Type | BTU Input Natural/Propane | | Energy Factor (E.F.) | | Annual Operating Cost | | Hot Water Output (GPM) | | |
|--------------|---------|---------------------------|---------|----------------------|---------|-----------------------|---------|------------------------|-----------|-----------|
| | | Minimum | Maximum | Natural | Propane | Natural | Propane | Maximum | 45°F Rise | 70°F Rise |
| GTU-140-NIH | Indoor | 15,000/13,000 | 120,000 | 0.93 | 0.93 | \$176 | \$421 | 6.6 | 5.0 | 3.2 |
| GTU-240-NIH | Indoor | 15,000/13,000 | 160,000 | 0.95 | 0.95 | \$172 | \$416 | 6.6 | 6.6 | 4.3 |
| GTU-340-NIH | Indoor | 15,000/13,000 | 180,000 | 0.95 | 0.95 | \$172 | \$416 | 8.0 | 7.6 | 4.9 |
| GTU-540-NIH | Indoor | 15,000/13,000 | 199,000 | 0.95 | 0.95 | \$172 | \$416 | 10.0 | 8.4 | 5.4 |
| GTU-140-NEH | Outdoor | 15,000/13,000 | 120,000 | 0.93 | 0.93 | \$176 | \$421 | 6.6 | 5.0 | 3.2 |
| GTU-240-NEH | Outdoor | 15,000/13,000 | 160,000 | 0.95 | 0.95 | \$172 | \$416 | 6.6 | 6.6 | 4.3 |
| GTU-340-NEH | Outdoor | 15,000/13,000 | 180,000 | 0.95 | 0.95 | \$172 | \$416 | 8.0 | 7.6 | 4.9 |
| GTU-540-NEH | Outdoor | 15,000/13,000 | 199,000 | 0.95 | 0.95 | \$172 | \$416 | 10.0 | 8.4 | 5.4 |

*For propane, change N to P in the model number when ordering. Example: GTU-140-PIH

U.S. Craftmaster® Water Heater Company reserves the right to make product changes or improvements without prior notice.

Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement.

