HYBRID ELECTRIC HEAT PUMP WATER HEATERS



- Available in 50-, 66-, and 80-Gallons nominal capacity
- 10-Year Limited Tank and Parts Warranty
- ENERGY STAR® qualified for many state and local utility rebates
- Uniform Energy Factor (UEF) ratings of 3.45
- Estimated Yearly Energy Cost as low as \$113
- Annual savings of \$305 or more compared to a conventional electric model*
- Super quiet operation 51 dBA versus competitive models
- 86-gallon First Hour Delivery meets Uniform Plumbing Code requirements for 6 bedroom/3.5 bath homes**
- Multiple operating modes allow the homeowner to optimize performance for efficiency and hot water delivery

*HPHE2K50HD045VUN compared to similarly performing conventional electric **HPHE2K80HD045VUN in Hybrid Mode

MORE FEATURES ON BACK







EASY-TO-USE ELECTRONIC INTERFACE

- User friendly, easy to read eye-level display
- · Easily select operating mode: Efficiency, Hybrid, Electric, Vacation
- Display communicates mode, set point, and displays service messages when applicable
- Vacation mode programmable up to 99 days

EFFICIENCY MODE

Utilizes the heat pump for all water heating for the most energy efficient operation*

HYBRID MODE

 Utilizes compressor as primary heat source, during periods of high demand heating elements will also be energized to provide supplementary heating*

ELECTRIC MODE

Standard electric water heater operation - utilizes heating elements for all water heating

VACATION MODE

Maintains tank temperature at 60°F during vacation or extended absence, up to 99 days, to reduce operating costs and provide freeze protection

*Automatically reverts to heating element only operation if entering air temperature is above 120°F, below 45°F or tank water temperature is below 60°F.

MORE FEATURES (continued from front)

- Accessory duct kit allows installation in confined spaces, may improve performance, and maintain comfort in occupied spaces of the home
- Long-lasting upper and lower backup heating elements
- Heavy-duty anode protects against tank corrosion
- Durable, tamper-resistant brass drain valve
- CSA certified and ASME rated temperature & pressure relief valve for safety
- Rated for 208 and 240 Volt power supply

Product Type	Model Number	Nominal Capacity Gallons	Rated Storage Volume Gallons	First Hour Delivery (Gallons)	Element Wattage (Standard)	Recovery 90° Rise - (Gallons per Hour)	Uniform Energy Factor	Diameter (inches)	Height to top of tank (inches)	Est. Yearly Energy Cost
Hybrid Electric Heat Pump, 10-Year Limited Warranty Tank/Parts, 1-Year Limited Warranty Labor [†]										
Tall	HPHE2K80HD045VUN	80	82	86	4500/4500	21	3.45	26 1/2	69	\$173
Tall	HPHE2K66HD045VUN	66	67	79	4500/4500	21	3.45	26 1/2	61	\$173
Tall	HPHE2K50HD045VUN	50	46	66	4500/4500	21	3.45	22	63	\$113

†For complete information consult written warranty.

Uniform Energy Factor and First Hour ratings shown for Hybrid Electric Heat Pump units are based on operation in the Hybrid mode. Recovery Ratings shown for Hybrid Electric Heat Pump units are based on back up heating element performance. Hybrid Electric Heat Pump units are rated for both 208 VAC and 240 VAC single phase power supply.

U.S. Craftmaster® Water Heaters reserves the right to make product changes or improvements without prior notice. Dimensions in all charts shown in inches. Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement. Some models may not be available in all markets.



Order Entry and Sales

500 Princeton Road (FEDEX, UPS) Johnson City, TN 37601-2030 P.O. Box 4808 (Mailing) Johnson City, TN 37602-4808 (800) 937-1037 FAX (800) 581-7224









Warranty and Service

500 Princeton Road (FEDEX, UPS) Johnson City, TN 37601-2030 P.O. Box 1597 (Mailing) Johnson City, TN 37605-1597 (800) 999-9515 FAX (800) 999-5210